

BEST AVAILABLE COPY

PN - JP4367892 A 19921221
PD - 1992-12-21
PR - JP19910170654 19910614
OPD - 1991-06-14
TI - EL DISPLAY ELEMENT
IN - SHIMIZU YOSHINORI
PA - NICHIA KAGAKU KOGYO KK
IC - G09F13/22 ; H05B33/14

© WPI / DERWENT

TI - EL display element with low power consumption - has pattern etched photosensitive resin layer on layer between back electrode and transparent electrode NoAbstract

PR - JP19910170654 19910614
PN - JP4367892 A 19921221 DW199305 G09F13/22 004pp
PA - (NICH-N) NICHIA KAGAKU KOGYO KK
IC - G09F13/22 ; H05B33/14
OPD - 1991-06-14
AN - 1993-041498 [05]

© PAJ / JPO

PN - JP4367892 A 19921221
PD - 1992-12-21
AP - JP19910170654 19910614
IN - SHIMIZU YOSHINORI
PA - NICHIA CHEM IND LTD
TI - EL DISPLAY ELEMENT

AB - PURPOSE: To make only necessary irreducible parts illuminate and to reduce the power consumption by forming a pattern-etched photosensitive resin layer between a back electrode and a transparent electrode.

- CONSTITUTION: The EL display element is constituted by laminating the back electrode 1, a reflective insulating layer 2, a fluorescent material film 3, the pattern-etched photosensitive resin layer 4, and the transparent electrode 5 in order. When the EL display element illuminates, a current becomes hard to flow since the pattern-etched photosensitive resin layer 4 is small in dielectric constant, so the layer does not illuminate and other parts are in the same structure with the EL display element therefore illuminates as bright parts to display characters, patterns, etc.

I - G09F13/22 ; H05B33/14